

Deep Learning based method to predict Plant Diseases: A case study with Rice Plant Disease Classification *

Mohammad Asifur Rahim¹, Rumana Akter², Ashif Reza³, Tauhidur Rahman⁴, Prof.Dr.Mohammad Shafiu Alam⁵
Computer Science and Engineering
Ahsanullah University of Science and Technology
Dhaka, Bangladesh
mohammadasifurrahim@gmail.com¹, rumananipa143@gmail.com²
ashifcse247@gmail.com³, rahmantauhidur33@gmail.com⁴, shafiu.cse@aust.edu⁵

Abstract—Bangladesh, a nation that largely depends on Rice for both its economy and dietary needs, is the target of the project, which intends to establish an easy and effective approach for recognizing rice plant diseases there. The research made use of an original dataset consisting of 5932 pictures of four various forms of Rice plant diseases. In order to extract features, we leveraged Convolutional Neural Networks (CNN) with Transfer Learning techniques and pre-trained models like VGG16, Inception-V3, VGG19, and ResNet-50. To increase the training and test accuracy, augmentation methods including flipping, zooming, and resizing the dataset were also performed. The VGG-19 model exceeded all other models with a test accuracy of 98%. Additionally, traditional machine learning models, including KNN, SVM, AdaBoost, Decision Tree, and Random Forest, were employed, with the Random Forest classifier achieving the highest accuracy of 96.6%. Gabor and Sobel filters were utilized for feature extraction before feeding the datasets into the machine-learning models. The suggested model performed better than the majority of earlier studies that have been done on Rice plant diseases in Bangladesh but used smaller datasets and showed lower performance levels.

Index Terms—Rice Plant Diseases, CNN, Transfer Learning, Gabor, Sobel

I. INTRODUCTION

Bangladesh is an agricultural country. Rice is a major food for the people of our country. Rice cultivation provides about 48%¹ of rural development. Around 75% of the overall harvested area and above 80% of the overall irrigated zone are cultivated through rice plants². Consequently, Rice plays an important role for the people of Bangladesh. But the quality and quantity of rice production may be decreased because of Rice plant Diseases. Having the disease in plants is quite natural. If proper step is not taken in this regard then it causes serious effects on Rice plants. Therefore, it is the major task to identify Rice plant Disease in the early stages. Early detection of Rice plant diseases is very crucial for the

crop protection system of our country.

At present, Most of the farmers of our country use their own experience to detect diseases, farmers use pesticides in excessive quantities which can not help in the prevention of disease but can have a malignant effect on plants. Thus their misclassification creates a bad impact on Rice cultivation. So, they need advice from rice disease specialists. In remote or rural areas, Rice disease specialists are not able to give quick remedies or advice to the farmers at the right time and they also require expensive equipment and a large amount of time for manually identifying and classifying rice diseases. Moreover, traditional visual observation methods are mostly inaccurate. Besides that laboratory testing requires time and can be expensive. The research that has been done on Bangladeshi Rice plant disease is not sufficient. Most of the research is done over a small number of datasets. Nowadays smartphones are available. If the farmers can somehow afford a smartphone it will be easier for them to use image-processing methods to detect Rice plant diseases. Therefore, an automated identification and classification system can help farmers to accurately detect plant diseases and take necessary measures beforehand.

Correspondingly, We tried to classify some severe Rice plant diseases leveraging machine learning and deep learning techniques. The use of advanced DL models to address the complexity and effectiveness of precision agriculture research in recent years [2] provides evidence that this is indeed the case. The following set of contributions to the research are made in light of our investigation.

- We focused on creating a customized CNN architecture that can get high accuracy in classifying four major Rice plant diseases from the leaves. Moreover, to overcome the small dataset issue augmentation techniques have been used to increase the size of the dataset which eventually resulted in getting higher accuracies in classifying

¹<http://www.knowledgebanc-brii.org/riceinban.php>

²<http://www.knowledgebanc-brii.org/riceinban.php>

diseases.

- We used unique feature extraction features in our images to get higher accuracies using machine learning models.
- Made a comparison analysis between our results and with other previous research as well where we got higher accuracies than most of the previous research.

II. RELATED WORKS

Md Jahid Hasan et al. [3] proposed a paper for rice disease identification and classification by integrating a support vector machine with a Deep Convolutional Neural Network (D-CNN). Transfer Learning techniques were used to improve the proposed model. The paper uses a complex AI system that integrates SVM and D-CNN for identifying rice plant diseases. The proposed model achieves an accuracy of 97.5%. However, the dataset used for training is a small collection of 1080 images and for testing, it was 270 images. The proposed methodology is best suited for a smaller number of images.

Tejas Tawde et al. [4] proposed a paper for rice plant disease detection and classification using Convolutional Neural Network (CNN) to distinguish different methods based on the classifier used. A hardware prototype and model using CNN are proposed.

Kawcher Ahmed et al. [5] proposed a model for rice leaf disease detection using machine learning techniques and CNN. They achieved over 97% accuracy when trained using KNN, Logistic Regression, j48, and Naive Bayes, but only 400+ images were used for the training process. Three plant diseases were detected and no deep-learning models were used. Image classification gives better accuracy with faster performance with deep learning models, but machine learning models used in this proposed model generally give a slower performance.

S Ramesh et al. [6] proposed a model for Rice Blast Disease detection and classification using a machine learning algorithm. Images were classified using ANN and K-Means Clustering. 99% accuracy was achieved for blast-infected images and 86% for healthy images. However, the model showed over-fitting tendencies due to only 300 leaf samples used as the dataset.

Anam Islam et al. [7] proposed a model for rice leaf disease recognition using Local threshold-based segmentation and Deep CNN. Three CNN architecture models VGG16, ResNet50, and Dense-Net121 are used for classification. A dataset of 786 images was used for training, with a testing accuracy of 78.84%.

S Ramesh et al. [8] proposed a model for the application of machine learning in the detection of blast disease in South Indian rice crops. K-means Clustering is used for image segmentation and an ANN classifier is used to determine whether an image is an image of an infected crop or not. The ANN classifier gave 99 accuracies for normal images and 100% for blast-infected images, but it only detects a single type of disease (Rice Blast). Other methods give a more accurate result.

Md. Sazzadul Islam et al. [9] proposed a model for the Identification of Various Rice Plant Diseases Using Optimized

Convolutional Neural Networks (CNN). 1677 images were used to increase the size of the dataset, and the model uses a depth-wise convolution to reduce computational cost and parameter size. However, a large number of classes is causing bias and misclassifications among some of the diseases with similar characteristics.

Vimal K. Shrivastava et al. [10] proposed a model for Rice Plant Disease Classification using a Deep Convolutional Neural Network (CNN) as a feature extractor and a Support Vector Machine (SVM) as a classifier. The accuracy achieved was 91.37% on a large ImageNet dataset of 1.2 Million Images 1000 classes was used, but a relatively small dataset of 619 images was used for identifying 3 types of rice diseases. The paper also mentioned the unavailability of labeled rice disease images.

III. METHODOLOGY

Traditional machine learning models and deep learning models as classifiers for comparison have both been used to detect plant diseases. The proposed model has been tested using five machine learning algorithms, including KNN, Adaboost, Decision Tree, Random Forest, etc in the classification step of classical machine learning. For classifiers using deep learning, for greater model accuracy, a customized CNN model and transfer learning approaches have been applied. Augmentation techniques have been applied to train the model with deep learning models. In the case of machine learning, a Gabor Filter [11] followed by a Sobel Filter [12] have been used for feature extraction purposes. Our work can be divided into two approaches. The two approaches are: • Rice plant Disease Classification using a machine-learning approach • Rice plant Disease Classification using a Deep Learning Approach

For both classification cases: some steps are followed: 1. Dataset Acquisition 2. Dataset pre-processing 3. Feature Extraction 4. Classification

The proposed method that we applied in our work is shown in Fig 1.

A. Dataset Acquisition

At first, we collected a suitable dataset [1]. The dataset contains 5932 images of 4 major Rice plant diseases in Bangladesh as well as other countries. Sample images of the datasets are shown in Fig 2.

B. Dataset pre-processing

The datasets are split into two sets which are training and validation/testing sets having a ratio of 80:20 respectively. The augmentation techniques are applied to the training dataset only. Here is the total data of 5932 images where 4745 images are used for training and 1187 images for testing. In training distribution, 1267 images for Bacterial Blight, 1152 for Blast, 1280 for Brown Spot, and 1046 for Tungro are used. In test distribution, 317 images for Bacterial Blight, 288 for Blast, 320 for Brown Spot, and 262 for Tungro are used.




Fig. 1. Schematic Diagram of our proposed work



Fig. 2. Sample images




Fig. 3. Augmented Images

C. Feature Extraction

The technique of turning raw data into numerical features that can be handled while keeping the information in the original data set is known as feature extraction. The interesting portions of an image are represented as a compact feature vector using feature extraction for image data.

1) *Feature Extraction for Machine Learning:* For feature extraction, the Gabor filter followed by a Sobel filter of size 3X3 is used. Here 256 filters are generated and convoluted over the training and testing images. For Gabor kernels, the kernel size is set to 5X5.

Gabor Features	Kernel Size	Theta	Sigma	Lambda	Gamma
256	5×5	0 - .78	1 & 3	0 - .78	.05 & .5

TABLE I
PARAMETERS OF GABOR KERNELS

1) *Normalization:* In image processing normalization, is a process that changes the range of pixel intensity values. The possible values for each pixel are 0 to 256. The computation of high numeric values may become more difficult when using the image as it is and running through a Deep neural network. So, the pixel values are normalized by dividing the values by 255 and converting them to a range from 0 to 1.

2) *Image Augmentation:* For deep networks to perform well, a lot of training data is required. Image Augmentation is typically needed to improve deep network performance in order to create a powerful image classifier with little training data. As deep neural networks need lots of training data to perform well, we increased the training samples by applying several processing techniques like rotation, shifts, flips, etc. We applied zoom-range=0.50 which means zoom-in and zoom-out by 50%. Moreover, the rotation range we set to 45, which means we randomly rotated each image between 0 and 45 degrees. We set the wide-shift range and height-shift range to 0.2. It means shifting the images along the X-axis and Y-axis by 20%. And finally, for mirror reflection, we set the horizontal flip=true. Some examples of augmented images are shown in Fig. 3.

Table I The Gabor features have been used over the training images for a total of 256 times for the Machine Learning model. With each iteration, the images undergo a feature extraction process based on the Gabor filter's different parameters. The filter uses parameters that control orientation(Theta), Phase Offset(Lambda), Gaussian Factor (Sigma), and Ellipticity(Gamma). All of these properties dictate the way how the information is extracted from the training images. This allows for the training to have images with highly crucial features required to detect the particular type of disease for a specific label. Figure 4 shows different stages of feature extraction with each iteration.

2) *Feature Extraction for Deep Learning:* For Deep learning models, the transfer learning technique was applied for feature extraction purposes. This is advantageous because many of the low-level traits that have been discovered from a large amount of immediately accessible data may be applied to tasks with less readily available data. Transfer learning is a common choice when there is a small amount of data on which to base the model. In Transfer learning, also known




Fig. 4. (From left to right)- Normal image, Seventh Stage of, 63th stage and 256th stage of Gabor Fea-tures

as ImageNet pre-training, a pre-trained network is improved upon using a new dataset or task. The practice of feature reuse, whereby features obtained from ImageNet are useful for other datasets or tasks, implicitly justifies the practice. We chose Vgg-16, Vgg-19, and Inception-V3 as our pre-trained model for feature extraction. We followed the strategy by keeping all the top layer's weights untrainable and feeding them to the classifier. We also built a custom CNN model for comparison purposes.

D. Model Architecture Of Proposed CNN Model

A custom CNN model has been proposed by our own to train the preprocessed dataset. The model consists of 11 layers of which 10 are hidden layers and 1 input and 1 output layer. The layers include a convolutional layer, pooling layer, flattened layer, and fully-connected or dense layer. Relu and Softmax activation functions are used.

Layer Name	Input Shape	Output Shape	Parameters
Conv2d-1	224X224X3	222X222X16	448
MaxPool-1	222X222X16	111X111X16	0
Conv2d-2	111X111X16	109X109X32	4640
MaxPool-2	109X109X32	54X54X32	0
Conv2d-3	54X54X32	52X52X64	18496
MaxPool-3	52X52X64	26X26X64	0
Flatten-1	26X26X64	43264	0
Flatten-2	43264	43264	0
Dense-1	43264	128	5537920
Dropuout	128	128	0
Dense-2	128	4	516

TABLE II
MODEL ARCHETECTURE OF CUSTOM CNN MODEL

IV. RESULT AND DISCUSSION

A. Performance Analysis for Machine Learning Models

1) *Random Forest*: The model used here for the performance analysis using machine learning is Random Forest.

Class Name	Precision	Recall	F1-score
Bacterial blight	0.95	0.99	0.97
Blast	0.99	0.90	0.94
Brown spot	0.96	0.99	0.98
Tungro	1.00	0.93	0.96
weighted avg	0.97	0.97	0.97

TABLE III
RESULT OF EVALUATION METRICS FOR RANDOM FOREST

Table III shows the precision, recall, and overall F1-score achieved for every individual disease type. The weighted average precision, recall and F1-score score this model showed

2) *KNN (K-Nearest Neighbour)*: KNN is one of the more simpler machine learning algorithms, which is classified by determining the neighbors around a certain label or class and the maximum Euclidean distance is considered for the label.

ClassName	Precision	Recall	F1-score
Bacterial blight	0.98	0.68	0.80
Blast	0.68	0.69	0.69
Brown spot	0.67	0.91	0.77
Tungro	0.95	0.50	0.65
weighted avg	0.80	0.75	0.75

TABLE IV
RESULT OF EVALUATION METRICS FOR KNN

Table IV shows the precision, recall, and F1-Score for all the classes.

3) *Adaboost*: Adaboost being an Adaptive boosting algorithm is used as an Ensemble method.

Class Name	Precision	Recall	F1-score
Bacterial blight	0.86	0.94	0.90
Blast	0.91	0.80	0.85
Brown spot	0.92	0.94	0.93
Tungro	0.95	0.86	0.91
weighted avg	0.90	0.90	0.90

TABLE V
RESULT OF EVALUATION METRICS FOR ADABOOST

The table V shows that the precision achieved for rice Tungro is the highest whereas the Brown spot gives the best recall score. Brown spot is observed to have the overall best score out of all other diseases.

4) *SVM (Support Vector Machine)*: The SVM algorithm is effective in cases where the number of dimensions is greater than the number of samples. However this machine learning algorithm works by putting data points, above and below the classifying hyperplane, so this means there is no probabilistic explanation for the classification.

Class Name	Precision	Recall	F1-score
Bacterial blight	0.81	0.94	0.87
Blast	0.90	0.47	0.62
Brown spot	0.78	0.93	0.85
Tungro	0.89	0.58	0.71
weighted avg	0.82	0.81	0.79

TABLE VI
RESULT OF EVALUATION METRICS FOR SVM

The table VI shows that Rice Blast has the most precise classification since there are a lesser number of false positives. However, in terms of recall, it shows an unsatisfactory value.

5) *Decision Tree*: Compared to other algorithms decision trees require less effort for data preparation during pre-processing.

ClassName	Precision	Recall	F1-score
Bacterial blight	0.97	0.89	0.93
Blast	0.91	0.80	0.85
Brown spot	0.94	0.93	0.94
Tungro	0.53	0.89	0.66
weighted avg	0.91	0.89	0.89

TABLE VII
RESULT OF EVALUATION METRICS FOR DECISION TREE

Here it is observed that the values are relatively less consistent compared to the deep learning models as shown in table XV.

Classifiers	Accuracy	Precision	Recall	F1-score
Random Forest	0.966	0.97	0.97	0.97
KNN	0.754	0.80	0.75	0.75
AdaBoost	0.902	0.90	0.90	0.90
SVM	0.81	0.82	0.81	0.79
Decision Tree	0.89	0.91	0.89	0.89

TABLE VIII
RESULT OF EVALUATION METRICS FOR MACHINE LEARNING MODELS

Among machine learning models, Random Forest shows the highest accuracy of **96.6%** and also shows the best metrics.

B. Performance Analysis for Deep Learning Models

The table displays the different combinations for batch sizes we have considered for better hyperparameter tuning. Adam has been Used as Optimizer, The Learning rate was set to .0001.

Class Name	Batch Size	Epoch	Accuracy (%)
Custom CNN	32	40	85
	16		88
	8		97
InceptionV3	32	40	89
	16		90
	8		98
VGG-16	32	40	91
	16		94
	8		97
VGG-19	32	40	89
	16		95
	8		98
ResNet-50	32	40	69
	16		65
	8		71

TABLE IX
HYPERPARAMETER TUNING

It can be observed in IX that the accuracy for all the deep learning models, shows better results for a batch size of 8.

1) *Custom Model*: The custom model proposed for the deep learning approach outperforms the pre-trained CNN model resnet=50 and gives equivalent results for all the other CNN models used for the deep learning approach. But the parameter

size for our custom model is around 5 million. This parameter size is much smaller compared to the pre-trained models used in this study. This makes the proposed model much more lightweight and easy to process compared to the other heavy CNN models.

Class Name	Precision	Recall	F1-score
Bacterial blight	0.91	1.00	0.95
Blast	1.00	0.88	0.94
Brown spot	1.00	1.00	1.00
Tungro	1.00	1.00	1.00
weighted avg	0.97	0.97	0.97

TABLE X
RESULT OF EVALUATION METRICS FOR CUSTOM MODEL

The table shows the superiority of the deep learning models compared to every machine learning model used in this study. The proposed custom model outperforms the random forest model and gives an accuracy of **97%**. Since this is a deep learning model it also performs much faster compared to the machine learning model.




Fig. 5. Training vs Validation (Accuracy & Loss) for Custom Model

Both the Accuracy and Loss graphs show that the training and validation move uniformly. The accuracy steadily increases and loss steadily declines. This is the desired behavior for a deep learning model. Besides some very minor fluctuations, the model performs very well throughout the training and validation process.

2) *VGG-19*: The pre-trained CNN model VGG-19 was chosen for the deep learning models in this study. Since this is a CNN model 19 layers deep, it has a large number of parameters (around 138 Million). Since every layer isn't important, they can be dropped. It is still a large number of parameters even after adding dropout. Since this is a model trained by millions of images, it performs very well as a CNN model.

Class Name	Precision	Recall	F1-score
Bacterial blight	0.99	0.98	0.99
Blast	0.99	0.94	0.97
Brown spot	0.95	1.00	0.98
Tungro	1.00	1.00	1.00
weighted avg	0.98	0.98	0.98

TABLE XI
RESULT OF EVALUATION METRICS FOR VGG-19

The evaluation metrics show that the precision and recall achieved for almost every disease are near-perfect for this model. It is observed that Rice Tungro gives a perfect score. Thus giving an accuracy of **98%** which is the highest accuracy achieved for a deep learning model.




Fig. 6. Training vs Validation (Accuracy & Loss) for **VGG-19**

The training vs validation graphs shows that the process does not yield any overfitting results. The validation accuracy and loss are uniformly increasing and decreasing respectively. This shows the result is near perfect with little to no false positives or negatives.

3) *InceptionV3*: InceptionV3 is one of the more preferred CNN models that are pre-trained. It has a deeper network compared to the Inception V1 and V2 models, but its speed isn't compromised. The efficiency of this model is really impressive. It is also computationally less expensive thus giving it a better edge against other CNN models.

Class Name	Precision	Recall	F1-score
Bacterial blight	0.99	0.99	0.99
Blast	0.92	1.00	0.96
Brown spot	1.00	0.93	0.96
Tungro	1.00	1.00	1.00
weighted avg	0.98	0.98	0.98

TABLE XII
RESULT OF EVALUATION METRICS FOR INCEPTIONV3

The table shows a clear idea that there is almost no false positives in terms of all the diseases. Rice Tungro seems to give perfect results for both precision and recall. So the accuracy for the InceptionV3 model is **98%** which is also the highest accuracy achieved out of all models.




Fig. 7. Training vs Validation (Accuracy & Loss) for **InceptionV3**

The training vs validation graphs shows that the process does not yield any overfitting results. The validation accuracy and loss are uniformly increasing and decreasing respectively.

This shows the result is near perfect with little to no false positives or negatives.

4) *Resnet-50*: This model has a very deep neural network of 50 layers as the name suggests. I. The Resnet-50 model is a complex network due to its depth. The main disadvantage of ResNets is that for a deeper network, the detection of errors becomes difficult.

Class Name	Precision	Recall	F1-score
Bacterial blight	0.70	0.75	0.73
Blast	0.73	0.35	0.47
Brown spot	0.76	0.80	0.78
Tungro	0.67	0.96	0.79
Weighted avg	0.72	0.71	0.69

TABLE XIII
RESULT OF EVALUATION METRICS FOR RESNET-50

When deeper networks are able to start converging, a degradation problem is exposed: with the network depth increasing, accuracy gets saturated (which might be unsurprising) and then degrades rapidly.




Fig. 8. Training vs Validation (Accuracy & Loss) for **Resnet-50**

The training and validation curves for both accuracy loss seem to be showing an increasing and decreasing trend. However, this seems to have lots of Fluctuations throughout the process. This means lots of false positives and false negatives have been classified here. This is why resnet-50 gives the least satisfactory result of **71%**

5) *VGG-16*: The other VGG network model used in our work is the VGG-16.

	Precision	Recall	F1-score
Bacterial blight	1.00	0.93	0.96
Blast	1.00	0.94	0.97
Brown spot	0.89	1.00	0.94
Tungro	1.00	1.00	1.00
weighted avg	0.97	0.97	0.97

TABLE XIV
RESULT OF EVALUATION METRICS FOR VGG-16

However, The total number of parameters in this model is over 138M, and the size of the model is over 500MB. Table XIV shows that the precision, recall and F1-score achieved using VGG-16 are around **97%**.

The training vs. validation graphs show that the process does not yield any overfitting results. The validation accuracy and loss are uniformly increasing and decreasing respectively up to 40 epochs.




Fig. 9. Training vs Validation (Accuracy & Loss) for VGG-16

C. Comparison Between Deep Learning Models

Classifiers	Accuracy	Precision	Recall	F1-score
Custom CNN	0.97	0.97	0.97	0.97
VGG-16	0.97	0.97	0.97	0.97
VGG-19	0.98	0.98	0.98	0.98
Inception-V3	0.98	0.98	0.98	0.98
ResNet-50	0.71	0.72	0.71	0.69

TABLE XV
RESULT OF EVALUATION METRICS FOR DEEP LEARNING MODELS

Table XV However, in this case, almost every model shows that the precision and recall values are similar. Besides ResNet-50, all the other models yield results **97%** and above. Resnet-50 produces the lowest accuracy with **71%**

D. Performance Comparison

Previously discussed, Anam Islam et al. [7] proposed a model using Local threshold-based segmentation and Deep CNN with 786 images for training, which achieved 78.84% accuracy. Similarly, Vimal K. Shrivastava et al. [10] used a Deep CNN as a feature extractor and SVM as a classifier with 619 images for training, which achieved 91.37%. Compared to that, the Custom CNN model proposed in this paper uses a large dataset of 5932 images which achieves an impressive **97%** accuracy.

Methodology	Dataset Size	Accuracy
Custom CNN	5932	97%
Vimal K. Shrivastava et al.	619	91.37%
Anam Islam et al.	786	78.84%

TABLE XVI
COMPARISON WITH PREVIOUS WORKS

V. CONCLUSION AND FUTURE WORK

Performance analysis of automated Rice plant disease classification is performed in our work. Moreover, five traditional classifiers are applied to classify Rice plant diseases in our images. Then a custom CNN model is designed on our own and applied to include deep learning in our work. Transfer Learning Techniques are applied in our work to get higher

accuracy. Here, a dataset consisting of 5932 images was used of four different Rice plant diseases. They have split into 80 and 20 ratios. Various experiments are applied over the datasets by tuning the parameters and hyperparameters of the model. And among them, the best ones are represented. Our custom CNN model produced an accuracy of 97 percent. There are more opportunities for improvement or research on our work in the future.

- First of all, dataset size can be increased. The bigger the number of images the better the model is trained
- More types of Rice plant diseases can be added to classify a variety of Rice plant diseases
- the system can be transformed into a web application or mobile Application. Using the mobile application farmers can automatically detect Rice plant diseases

REFERENCES

- [1] Sethy, Prabira Kumar. "Rice Leaf Disease Image Samples." Mendeley Data, V1, doi: 10.17632/fwj7stb8r.1, 2020.
- [2] Spyridon Mourtzinis, Paul D. Esker, James E. Specht, Shawn P. Conley. "Advancing agricultural research using machine learning algorithms" *Scientific Reports*, 2023.
- [3] Hasan, Md Jahid, Mahub, Shamim Alom, and Md. Shahin Nasim. "Rice Disease Identification and Classification by Integrating Support Vector Machine With Deep Convolutional Neural Network." In *2019 International Conference on Advanced Systems in Electrical Engineering and Computer Science (ICASECS)*, pp. 1-6, doi: 10.1109/ICASECS.2019.8934568, 2019.
- [4] Tawde, Tejas, Kunal Deshmukh, Lobhas Verekar, Ajay Reddy, Shailendra Aswale, and Pratiksha Shetgaonkar. "Rice Plant Disease Detection and Classification Techniques: A Survey." *International Journal of Engineering Research Technology (IJERT)*, Volume 10, Issue 07, 2021.
- [5] Ahmed, K., Shahidi, T. R., Alam, S. M. Irfanul, and Momen, S. "Rice Leaf Disease Detection Using Machine Learning Techniques." In *International Conference on Sustainable Technologies for Industry 4.0 (STI)*, pp. 1-5, doi: 10.1109/STI47673.2019.9068096, 2019.
- [6] Ramesh, S. "Rice Blast Disease Detection and Classification Using Machine Learning Algorithm." In *2018 International Conference on Modern Electrical and Energy Systems (ICMEES)*, pp. 255-259, doi: 10.1109/ICMETE.2018.00063, 2018.
- [7] Islam, Anam, Redoun Haque, S. M. Rafizul Islam, S.M. Khan, and Mohammad. "Rice Leaf Disease Recognition using Local Threshold Based Segmentation and Deep CNN." *International Journal of Intelligent Systems and Applications*, 13, pp. 35-45, 2021.
- [8] Ramesh, S., and Vydek, D. "Application of machine learning in the detection of blast disease in South Indian rice crops." *International Journal of Advanced Research in Computer and Communication Engineering*, 6, issue. 4, 2017.
- [9] Prottasha, Md. Sazzadul Islam, A. B. M. Kabir Hossain, Md. Zihadur Rahman, S M Salim Reza, and Dilshad Ara Hossain. "Identification of Various Rice Plant Diseases Using Optimized Convolutional Neural Network." 2021.
- [10] Shrivastava, V. K., Pradhan, M. K., Minz, S., and Thakur, M. P. "Rice Plant Disease Classification Using Transfer Learning of Deep Convolutional Neural Network." 2019.
- [11] Sourabh Kumar Kashyap1, Jitendra Kumar Mishra2 "A Review Paper on Gabor Filter Algorithm for The application of Texture Segmentation." , 2008.
- [12] Dibya Jyoti Bora. "A Novel Approach for Color Image Edge Detection Using Multidirectional Sobel Filter on HSV Color Space." 2017.